

MoveFlow Hybrid

- Design essenziale e compatto con modelli alternativi per un'ampia varietà di applicazioni
- Sono disponibili diversi moduli integrati di pagamento in contanti, oltre ai pagamenti con carta
- A prova di errori e tentativi di frode grazie alla bilancia per la convalida degli acquisti
- Hybrid: una soluzione compatta e intelligente che offre la flessibilità del passaggio dalla cassa manuale alla cassa automatica









Technical specification

Dimensions HxLxW mm	Width: 795 - 1775 mm Depth: 625 mm Height: 1365 mm
Weight kg	170 - 200kg
Certifications	CE
Voltage	220-240VAC 50-60Hz Max 3A in total
Operating temperature	+10 °C to +30 °C
Customer display	Yes
Options	Yes
Packing area alternatives	Wing Sizes: X1 / X2
Payment options	Card & Glory / OEM prepared
Ergonomic norms	ADA guidelines
Customisable	Yes
Installation	Indoor
Scanners	3450
Security solution	Weight verification by security scale
Operating conditions	Ambient humidity: 30-80% Storage humidity: 30-80%

ITAB HQ Sweden
Phone: +46 36 31 73 00
info@itab.com

Local contact
Please visit
www.itab.com/contact

Please note that this product sheet is for a specific product and colour. The pictures may show examples of other available colours.