# CheckMate Tandem

- Ergonomisch ontworpen om het bereik en onnodige bewegingen te minimaliseren.
- Eenvoudige installatie
- Geschikt voor de gangbare kassa's en betaalsystemen.
- De checkout kan worden voorzien van een rollertafel of een kassaband of –rollers met weegschaal.
- Een uitgebreid administratiegedeelte, van alles voorzien: van een centrale verwerkingsunit tot een vuilnisbak.



## Technical specification

| | |
|---|---|
| Dimensions HxLxW mm | Length: 2500-2950 mm Width:1250 mm Height: 970 mm |
| Certifications | CE |
| Voltage | 220-240VAC 50-60Hz Max 3A in total |
| Operating temperature | +10 °C to +30 °C |
| Customer display | Yes |
| Options | Yes |
| Packing area alternatives | Dual lane |
| Payment options | Cash & Card payment/Prepared for CG/Prepared for Safepay |
| Ergonomic norms | Applicable to swedish recommendations ADI566 |
| Customisable | Yes |
| Installation | Indoor |
| Scanners | Dimensions prepared for Magellan 3200V &3450 |
| Operating conditions | Ambient humidity: 30-80% Storage humidity: 20-90% |

**ITAB HQ Sweden**
Phone: +46 36 31 73 00
info@itab.com

**Local contact**
Please visit
www.itab.com/contact

Please note that this product sheet is for a specific product and colour. The pictures may show examples of other available colours.