MoveFlow Classic

- Un design dépouillé et minimaliste avec des modèles alternatifs pour un large éventail d'applications (X1, X2, Mini).
- Une protection contre les erreurs et les tentatives de fraudes grâce à une balance de vérification des achats.
- Des solutions de paiement par carte intégrées pour un encombrement minimal, mais une fonctionnalité optimale.
- Un aspect personnalisable avec vernis possible dans toutes les teintes RAL.
- Selon le modèle, la caisse MoveFlow Classic peut être dotée de différentes configurations de rayonnages.







Technical specification

Dimensions HxLxW mm	Width: 795 - 1775 mm Depth: 625 mm Height: 1365 mm
Weight kg	80 - 140kg
Certifications	CE/UL
Voltage	220-240VAC 50-60Hz Max 3A in total
Operating temperature	+10 °C to +30 °C
Customer display	Yes
Options	Yes
Packing area alternatives	Wing Sizes: Mini / X1 / X2
Payment options	Card Payment
Ergonomic norms	ADA guidelines
Customisable	Yes
Installation	Indoor
Scanners	3550, 9300 and 9800
Security solution	Weight verification by security scale
Operating conditions	Ambient humidity: 30-80% Storage humidity: 30-80%

ITAB HQ Sweden
Phone: +46 36 31 73 00
info@itab.com

Local contact
Please visit
www.itab.com/contact

Please note that this product sheet is for a specific product and colour. The pictures may show examples of other available colours.