CheckMate Z

- Kassapöydän etuosa kohti asiakasta
- Parempi näkyvyys kassajonon suuntaan
- Nopeampaa asiakaspalvelua pikakassa-asiakkaille
- Suunniteltu ergonomian maksimoimiseksi
- Pieni ja suoraviivaisesti muotoiltu syöttölinja auttaa kassatyöntekijää käsittelemään ostoksia nopeammin







Technical specification



Dimensions HxLxW mm	Length: 4360 - 6000 mm Width: 1660 mm Height: 970 mm
Certifications	CE
Voltage	220-240VAC 50-60Hz Max 3A in total
Operating temperature	+10 °C to +30 °C
Customer display	Yes
Options	Yes
Packing area alternatives	Dual lane with 3rd customer functionality
Payment options	Cash & Card payment/Prepared for CG/Prepared for Safepay
Ergonomic norms	Applicable to swedish recommendations ADI566
Customisable	Yes
Installation	Indoor
Scanners	Dimensions prepared for Magellan 3200V &3450
Operating conditions	Ambient humidity: 30-80% Storage humidity: 20-90%





ITAB HQ Sweden
Phone: +46 36 31 73 00
info@itab.com

Local contact
Please visit
www.itab.com/contact

Please note that this product sheet is for a specific product and colour. The pictures may show examples of other available colours.