AlphaGate

- Automatische reset poortarm (nadat de paniekfunctie is uitgeschakeld).
- 0° tot 180° werking.
- Reinigingsmodus - alle poortjes kunnen tegelijkertijd worden geopend vanaf een optioneel bedieningspaneel, om schoonmaakmachines en leveringen door te laten.
- Koppeling aan brandalarm om het openen van een poort te activeren.
- Koppeling aan brandalarm om het openen van een poort te activeren. Het poortje heeft een verstelbare paniekfunctie..





Technical specification

Dimensions HxLxW mm	1117x120x120
Weight kg	23 kg + gate arm
Certifications	CE/UL
Voltage	115-240VAC 50-60Hz
Operating temperature	0-35° C
Automatic Panic Reset	Yes
Gate Arm options	Yes
LED light	Optional
Opening angle	180 degrees
Synchronized opening	Yes
Panic Alarm	Yes
Communication	Optional
Options	Remote control, overhead sensor, service desk switch, RFID reader
Customisable	Yes
Installation	Indoor
Operating conditions	Indoor

ITAB HQ Sweden
Phone: +46 36 31 73 00
info@itab.com

Local contact
Please visit
www.itab.com/contact

Please note that this product sheet is for a specific product and colour. The pictures may show examples of other available colours.