



MoveFlow Hybrid

ITAB

- ✓ Design essenziale e compatto con modelli alternativi per un'ampia varietà di applicazioni.
- ✓ Sono disponibili diversi moduli integrati di pagamento in contanti, oltre ai pagamenti con carta.
- ✓ A prova di errori e tentativi di frode grazie alla bilancia per la convalida degli acquisti.
- ✓ Aspetto adattabile con finitura laccata a scelta in qualsiasi colore RAL o serie di colori.
- ✓ Configurazioni aggiuntive di stoccaggio e scaffalatura disponibili per alcuni modelli.



Technical specification

Dimensions HxLxW mm	Width: 795 - 1775 mm Depth: 625 mm Height: 1365 mm
Weight kg	170 - 200kg
Certifications	CE
Voltage	220-240VAC 50-60Hz Max 3A in total
Operating temperature	+10 °C to +30 °C
Customer display	Yes
Options	Yes
Packing area alternatives	Wing Sizes: X1 / X2
Payment options	Card & Glory / OEM prepared
Ergonomic norms	ADA guidelines
Customisable	Yes
Installation	Indoor
Scanners	3450
Security solution	Weight verification by security scale
Operating conditions	Ambient humidity: 30-80% Storage humidity: 30-80%

ITAB HQ Sweden

Phone: +46 36 31 73 00
info@itab.com

Local contact

Please visit
www.itab.com/contact

Please note that this product sheet is for a specific product and colour. The pictures may show examples of other available colours.