
CheckMate Tandem



- Diseñado ergonómicamente para minimizar el alcance y los movimientos innecesarios
- Instalación sencilla
- Preparado para los registros y sistemas de pago más comunes
- La caja puede estar equipada con una mesa de rodillos, una balanza de cinta o una balanza de rodillos
- Una generosa zona de administración, preparada para todo: desde una unidad central de procesamiento a un cubo de basura

Technical specification

Dimensions HxLxW mm	Length: 2500-2950 mm Width:1250 mm Height: 970 mm
Certifications	CE
Voltage	220-240VAC 50-60Hz Max 3A in total
Operating temperature	+10 °C to +30 °C
Customer display	Yes
Options	Yes
Packing area alternatives	Dual lane
Payment options	Cash & Card payment/Prepared for CG/Prepared for Safepay
Ergonomic norms	Applicable to swedish recommendations ADI566
Customisable	Yes
Installation	Indoor
Scanners	Dimensions prepared for Magellan 3200V &3450
Operating conditions	Ambient humidity: 30-80% Storage humidity: 20-90%

ITAB HQ Sweden
Phone: +46 36 31 73 00
info@itab.com

Local contact
Please visit
www.itab.com/contact

Please note that this product sheet is for a specific product and colour. The pictures may show examples of other available colours.