



- ✓ Brann- og sikkerhetskompatibel med patentert panikk-funksjon.
- ✓ Minimalt fotavtrykk takket være slank design og skyvedører.
- ✓ Enkel installasjon med trådløs portkommunikasjon.
- ✓ Inngår i en etablert portefølje av porter, tilgjengelig i tre størrelser.
- ✓ Fjernovervåking og konfigurasjon via OnRed-plattformen.\*



## Technical specification

Dimensions HxLxW mm	900 (pair): 1125x2202x140 900 High (pair): 1812x2202x140 1200 (pair): 1125x2802x140
Weight kg	900/900 high/1200 (pair): 140/178/158 kg
Certifications	CE
Voltage	24 VAC, 110-240 VAC
Operating temperature	0-35
Automatic Panic Reset	Yes
Gate Arm options	Yes
LED light	Yes, Customisable color for gate body and gate arm
Synchronized opening	Yes, wireless
Panic Alarm	Yes
Communication	Cloud connectivity through OnRed
Options	Remote control, Connection to fire alarm. Overhead sensor, Service desk switch, RFID reader
Customisable	Yes, Color of gate body, LED-color, Gate arm Logo
Installation	Indoor
Scanners	Optional
Security solution	Radar options, Gate arm options
Sustainability	49,5% lower Carbon footprint than SigmaGate 1
Operating conditions	Indoor