


- ✓ Hallitse ja mukauta porttejasi vaivattomasti OnRed-alustan avulla mistä tahansa.
- ✓ Helppo asentaa langattoman viestinnän ansiosta, ei enää sotkuisia kaapeleita.
- ✓ Säästä energiaa ajastamalla portin ECO-tila myymälän aukioloaikojen mukaan.
- ✓ Saat reaaliaikaiset ilmoitukset suoraan OnRedin kautta - Pysyt aina ajan tasalla.
- ✓ Kustomoi LED-valaistus ja portin värit brändisi mukaisiksi ja luo näyttävä ensivaikutelma.



Technical specification

Dimensions HxLxW mm	1125*120*120 (foot plate 182)
Weight kg	16
Certifications	CE
Voltage	24 VAC, 110-240 VAC
Operating temperature	0-35° C
Automatic Panic Reset	Yes
Gate Arm options	Yes
LED light	Yes, Customisable colour for gate body and gate arm
Opening angle	180°
Synchronized opening	Yes
Panic Alarm	Yes, with possibility to real time notification via OnRed
Communication	Cloud connectivity through OnRed, Remote control, Connection to fire alarm
Options	Overhead sensor, Service desk switch, RFID reader
Customisable	Yes, Colour of gate body, LED-colour, Gate arm Logo
Installation	Indoor
Scanners	Optional. ScanMaster or ScanMaster XD
Security solution	Radar options, Gate arm options and possibility to real time notification via OnRed
Operating conditions	Indoor