


- ✓ Gérez et configurez facilement vos portillons via la plateforme OnRed, où que vous soyez.
- ✓ Profitez d'une installation facile grâce à la communication sans fil par portillon, éliminant ainsi le besoin de câbles encombrants.
- ✓ Programmez le mode ECO, les réglages d'ouverture permanente et enregistrez les heures de fonctionnement pour optimiser l'efficacité.
- ✓ Réglages d'alarme personnalisés avec alertes et notifications en temps réel via OnRed.
- ✓ Personnalisez les couleurs des LED et des portillons pour les adapter à l'image de marque de votre magasin.



Technical specification

Dimensions HxLxW mm	1125*120*120 (foot plate 182)
Weight kg	16
Certifications	CE
Voltage	24 VAC, 110-240 VAC
Operating temperature	0-35° C
Automatic Panic Reset	Yes
Gate Arm options	Yes
LED light	Yes, Customisable colour for gate body and gate arm
Opening angle	180°
Synchronized opening	Yes
Panic Alarm	Yes, with possibility to real time notification via OnRed
Communication	Cloud connectivity through OnRed, Remote control, Connection to fire alarm
Options	Overhead sensor, Service desk switch, RFID reader
Customisable	Yes, Colour of gate body, LED-colour, Gate arm Logo
Installation	Indoor
Scanners	Optional. ScanMaster or ScanMaster XD
Security solution	Radar options, Gate arm options and possibility to real time notification via OnRed
Operating conditions	Indoor