


- ✓ Hantera och konfigurera enkelt dina grindar via OnRed från vilken plats som helst.
- ✓ Njut av enkel installation med trådlös grindkommunikation och slipp behovet av otympliga kablar.
- ✓ Schemalägg ECO-löge, butikens öppettider och permanenta öppningsinställningar för att optimera effektiviteten.
- ✓ Skräddarsydda larminställningar med varningar och notifikationer via OnRed i realtid.
- ✓ Anpassa LED-färger och grindfärger för att matcha butikens varumärke.



## Technical specification

Dimensions HxLxW mm	1125*120*120 (foot plate 182)
Weight kg	16
Certifications	CE
Voltage	24 VAC, 110-240 VAC
Operating temperature	0-35° C
Automatic Panic Reset	Yes
Gate Arm options	Yes
LED light	Yes, Customisable colour for gate body and gate arm
Opening angle	180°
Synchronized opening	Yes
Panic Alarm	Yes, with possibility to real time notification via OnRed
Communication	Cloud connectivity through OnRed, Remote control, Connection to fire alarm
Options	Overhead sensor, Service desk switch, RFID reader
Customisable	Yes, Colour of gate body, LED-colour, Gate arm Logo
Installation	Indoor
Scanners	Optional. ScanMaster or ScanMaster XD
Security solution	Radar options, Gate arm options and possibility to real time notification via OnRed
Operating conditions	Indoor

